

## Vinyl Blower Duct



### Vinyl Blower Duct

An economical duct for large volume air transfer. This fabric reinforced vinyl coated blower duct is ideal for fresh air supply. Blower duct is manufactured without glues and adhesives, will not delaminate. It is reinforced with a molecularly bonded wear strip for scuff resistance and a spring steel helix covered with a urethane wear strip for maximum abrasion resistance.

#### Applications

Large Volume Air-conditioning  
Large Volume Heating  
Fresh air ventilation for utility manholes  
Fresh air supply for aviation cleaning  
meets NFPA 701 and ULC S-109 large scale test requirements for flame retardancy

#### Special Features

Standard plain ends  
Optional "attached soft cuffs"  
Optional buckles  
Scuff resistant  
Economical  
Compressible and flexible

#### Construction

Material: Polyester single fabric coated with vinyl  
Construction: Single ply fabric over fully encapsulated spring steel helix with urethane wear strip  
Diameters: 6" to 24" I.D. Large sizes available  
O.D. : I.D. + 3/8"  
Bend Radius = 12" diam = 7"  
Pitch: 6"  
Weight: 6" I.D. = .7 lbs/ft  
Compression Ratio: 10:1  
Length: 25 ft  
Temperature Range: -20°F to +180°F  
Color: Yellow with black scuff guard  
Larger diameters and custom colors available upon request with a minimum order quantity.

Berlin, NJ  
Indianapolis, IN  
Haw River, NC  
Whitby, ON

Tel 856.768.2275  
Tel 317.334.1444  
Tel 336.578.2161  
Tel 905.666.4970

Fax 856.768.2385  
Fax 317.334.1535  
Fax 336-578.5554  
Fax 905.666-9388

800.225.0215  
800.526.6288  
800.334.4270

THE  
**NOVAFLEX**  
GROUP 

Email: [sales@novaflex.com](mailto:sales@novaflex.com)  
Website: [www.novaflex.com](http://www.novaflex.com)